



EBW100-LAN



With the EBW100-LAN you can also easily visualize and manage application data via the Cumulocity Cloud and the Telekom “Cloud der Dinge”.

Professional routers for secure and easy network connection

The EBW100-LAN is a high-quality dial-in / dial-out router with netmapping and port forwarding for the remote maintenance of your ethernet applications.

Reduction to the essentials

The EBW series of INSYS icom is characterised by deliberate reduction to standard routing tasks without stinting on quality and IT security. EBW devices consist of a router and feature an integrated Linux programming environment for user-specific applications (INSYS sandbox).

The EBW100-LAN decouples for example manufacturing cells with remote access from the surrounding company IT. Also many subnetworks with identical local IP addresses can be differentiated and addressed specifically.

Safe and easy via VPN

Configuration is accomplished via a simple and intuitive web interface. The combination of VPN and firewall provides a maximum of IT security. You'll set-up your own VPN network quick and easy with the optional DELTA LOGIC Connectivity Service. PCs, routers and locally connected network devices can be integrated in just a few steps.

Extensions for monitoring, alerting and cloud services

The Monitoring App allows you to extend the functionality of the devices by monitoring controls and other devices as well as sending messages via e-mail or SMS.

Moreover, application data can be transferred quick and easy to cloud services like Cumulocity or Telekom “Cloud der Dinge” for central management and visualisation.

Technical highlights

- Compact design
- IT security: VPN, stateful firewall
- 2-port switch with 10/100 MBit/s
- Integrated Linux programming environment (INSYS sandbox)
- Monitoring App for monitoring Siemens LOGO!™, S7 and Modbus TCP devices available
- Management and visualisation of application data via Cumulocity Cloud and Telekom “Cloud der Dinge”
- Quick start for DELTA LOGIC Connectivity Service

EBW100-LAN

Technical details

Router

Function	IPv4/IPv6 router, connection management, DHCP server and client, Full NAT (IP forwarding, port forwarding, netmapping), DNS relay, dynDNS support, PPPoE for ADSL modem via LAN (ext), Dial-in, dial-out, callback
Security	OpenVPN (client and server), IPsec (ESP normal/aggressive mode), GRE, PPTP, stateful firewall and MAC filters, RADIUS authentication, 10 users for dial-in, authentication via PAP/CHAP/MS-CHAP/MS-CHAP 2, dial filter for dial-out, linkloss detection, failed login detection, no backdoor
Redundancy	LAN ext. port for external DSL modem, 2 dial-out targets, 2 OpenVPN servers
Connection stability	Connection monitoring on several levels, hardware watchdog

Operation

Configuration	Local and remote web interface (http, https), command line interface (CLI), Telnet, SSH, ASCII and binary file (also for backup), quick start for DELTA LOGIC Connectivity Service Menu languages: German, English, French
Indications (LEDs)	Connection status, data/signal, device status/VPN, power, switch ports
Diagnosis	log files, support package, integrated help functions, Diagnosis tools: ping, tcpdump, traceroute, DNS lookup
Customer-specific programming environment	User access to embedded Linux (sandbox), 150 MB permanent memory, socket access, example programs: e-mail and SMS client, serial logger, etc.
Messages	Hardware watchdog, system messages via e-mail, SNMP traps, SNMP V1/V2c/V3
Additional features	NTP client and server, buffered real-time clock, optional monitoring packages
Updates	Update of firmware and configuration (local and remote), daily auto update via server (http, ftp)



Monitoring app for monitoring Siemens LOGO!™, S7 and Modbus TCP devices usable in addition. More information at:

www.deltalogic.de/produkte/fernwartung/monitoring-app

EBW 100-LAN



Create VPN connection easily and securely. With the DELTA LOGIC Connectivity Service.

<https://connectivity.deltalogic.de>

Environmental conditions

Power supply	10 ... 48 V DC (±20%)
Power consumption (during connection)	Approx. 2 W
Operating temperature	-30...+60 °C -30...+85 °C under restricted conditions (refer to www.insysicom.com/restricted)
Humidity	0...95% (non-condensing)
Mounting/protection class	DIN rail mounting / housing: IP40, terminals: IP20
Certifications	CE, IC and FCC part 15 class A
Applied standards	Radiation: EN 55022 Class B, EN 61000-6-3 Interference resistance: EN 55024, EN 61000-6-2
Dimensions (W x H x D)	45 x 70 x 110 mm (2,6 HP)

Monitoring App (monitoring function)

Monitoring elements	Timer, internal flags
Logical combination of the elements	AND, OR, NOR, NAND, XOR
Actions	Message dispatch, http call, timer start, upload to Cumulocity cloud, Telekom "Cloud der Dinge": Central and easy visualisation of measurements, events and alarms
Messages	SMS, e-mail: Freely configurable text, also actual values from monitored elements